

PEACOCK T-WASH (Low VOC)

Product Code: 6506

Date: Feb 2012 (Page 1 of 1)

PRODUCT DESCRIPTION

- T-Wash primer is a mordant solution which contains phosphoric acid and volatile solvent it provides rough surface to improve adhesion of subsequent painting system by chemical reaction with substrate
- As a pretreatment agent for use on galvanized steel

PHYSICAL PROPERTIES

Colour and gloss	Light blush colored liquid
Mass density	approx. 1.0g/cm ³
Theoretical spreading rate	20~30 m ² /l
Touch dry (at 20⁰C)	20~60 mins
Overcoating interval	When surface is dried rinsing with water. After application of Peacock T-Wash primer, unreacted mordant solution should be removed by rinsing with water or scrubbing with the rag soaked in water.
Flash point (Din 53212)	35 ⁰ C
VOC	<400 g/litre

APPLICATION CONDITIONS AND TEMPERATURE

- Remove oil, grease and other contaminations from the surface to be coated with suitable solvent

APPLICATION INSTRUCTION

- Application by brush or spray
- When properly applied, this solution turns the bright surface to black and rough depends on substrate
- If such discoloration does not occur it is a sign that the pretreatment has not been effective
- This may be due to the surface being covered with grease, flux or other contaminants, or to the presence of anti-white rust or wet storage, stain treatment
- It will be necessary to remove unreacted mordant solution and contaminants before re-applying of the mordant solution

SAFETY NOTICE

- This product contains strongly acidic ingredient
- For application, use polyethylene bottle or plastic container
- Avoid contact with skin and eyes
- Avoid prolonged breathing of solvent vapors
- Use with adequate ventilation
- If the product comes in contact with the skin, wash thoroughly with a suitable industrial cleanser, or otherwise with lukewarm water and soap. If the eyes are contaminated, wash out with water for at least 10 minutes and seek for medical attention at once